

Heating Foil Mat 140W



Our 140W/m² underfloor heating foil mats are the perfect solution to providing sole source floor warming to floating laminate and engineered wood floor finishes. Featuring an aluminium dissipation layer which helps to spread the heat out evenly from the cable.

The Heating Foil Mats must be fitted onto Amber-XPS 6mm insulation boards for the system to properly distribute the heat across the floor.



Range (140W)			
Length of the Mat (mtr)	Width of the Mat (mm)	Area Sq M	Watts (W)
2	500	1.0	140
3	500	1.5	210
4	500	2.0	280
5	500	2.5	350
6	500	3.0	420
7	500	3.5	490
8	500	4.0	560
9	500	4.5	630
10	500	5.0	700
12	500	6.0	840
14	500	7.0	980
16	500	8.0	1120
18	500	9.0	1260
20	500	10.0	1400

Benefits

- Simple Installation
- Removes Latex Requirement
- 100% Earth Shield
- 3 Metre Cold Tail
- 10 Year Warranty

Specifications	
Construction	Aluminium Foil Heater with Twin Conductor having primary insulation of FluoroPolymer, Sandwiched between 2 layers of Specially Reinforced Aluminium Foil.
Standard Wattage	80 W/Sq.Mt and 140 W/Sq.Mt
Width of the mat	500mm
Heating Cable Spacing	50mm
Cold lead	3.0 M